## MAHARSHI DAYANAND UNIVERSITY ROHTAK (Established under Haryana Act No. 25 of 1975) 'A+' Grade University accredited by NAAC

## DEPARTMENT OF FORENSIC SCIENCE

No.FS/202 $\frac{371-79}{2}$ Dated; - 13/01/23

0/0		
/		

Dear Sir/Madam

To.

Please quote for article mentioned below in the list attached herewith so as reach undersigned by  $27 \frac{14}{20} \frac{7}{20} 3$ 

THE QUALITY, MAKE, PACKING and other particulars of each item should be stated. WHILE SUBMITTING THE QUOTATIONS PLEASE NOTE THE POINTS MENTIONED BELOW: -

- 1. The quotations are to be sent in an envelope marked QUOTATION DUE ON <u>21<sup>th</sup></u> <u>Jan 2023</u> and this envelope may be put in another envelope addressed to the undersigned.
- 2. The rates of S.T./ C.S.T., EXCISE, CUSTOM and other takes chargeable must be specified.
- 3. The rates of insurance, if any, should be specified. The firm will be required to submit the original Payee Receipt along with the bill.
- 4. Please state the time period within which the items will be supplied.
- 5. GUARANTEE PERIOD OF THE INSTRUMENTS MUST BE MENTIONED.
- 6. Discount if any, is to be given with the quotation.

Sr. No.	Name of Item	Specifications
1.	Stereo-zoom camera and display unit	<ul> <li>9.7" High resolution touch screen, 5.0-megapixel camera with C mount in-build software</li> <li>USB Digital camera with C mount and software</li> <li>Supported with HDMI output</li> <li>USB storage with SD card storage facility</li> </ul>
2.	Electrode for pH meter model ION 2700 pH meter (Oakton)	<ul> <li>Range- 0-13 pH</li> <li>Temperature- 0-100 °C material glass</li> <li>Measuring section size: φ12 x 110mm</li> <li>Liquid junction material: Ceramic</li> <li>Inner pole: Ag/AdCl</li> <li>BNC connector type</li> <li>Double junction, Refillable</li> </ul>
3.	Vortex shaker/mixer	<ul> <li>Adjustable speed from 300 to 4200 RPM &amp; timer setting</li> <li>Digital display – Shows speed and time alternatively at every 5 secs</li> <li>User enabled run time and off time setting</li> <li>3-way switch (On/Off/Touch) with Power On LED</li> <li>Orbital diameter of 4 mm</li> </ul>
4.	Data logger with probe	<ul> <li>Temperature accuracy: -30°C~+60°C;</li> <li>Temperature accuracy: -30°C~+60°C,</li> </ul>

(Temperature & Humidity)	<ul> <li>Humidity range: 0~99%RH</li> <li>Humidity accuracy: ±3%RH (25°C,20~90%RH),</li> <li>Record data capacity: RC-4HA 8000 points</li> <li>Record interval: 10 s~24 hour adjustable</li> <li>Battery life: if the record interval sets as 15 minutes it could be used above one year.</li> </ul>
-----------------------------	--

Yours Sincerely,

Head, Deptt. Of Forensic Science M.D. University, Rohtak Head Department of Forensic Science Maharshi Dayanand University Rohtak-124001 (Haryana)