

**MAHARSHI DAYANAND UNIVERSITY, ROHTAK**  
**NOTICE INVITING QUOTATIONS**

Sealed percentage/item rate quotations are hereby invited by the undersigned for and on behalf of Registrar, M.D. University, Rohtak for the below noted work from the suppliers/Agencies/Contractors/societies registered with Haryana P.W.D. B & R. M.E.S. & Central P.W.D. UHBVN/DHBVN or any other State/Central Govt. Department for electrical works on dated 01/09/2023 at 3 PM. Quotations will be opened at the same date and time in the presence of quotationers or representative who may like to be present at that time. However, preference will be given to societies first, if two or more societies participated and found eligible. DNIQ may be seen on University website or in the office of Sub-Division.

Description	App.Amt.	Earnest Money	Time Limit
S/E of LED false ceiling light 36 watt for Admin Block VIET, Room No. 205, Pharmacy Science & G-23 Lab Genetic Department in MDU, Rohtak.			43320/-

Conditions: -

1. The work will be carried out strictly in accordance with the PWD Haryana specification and approved DNIQ.
2. 5% Security will be deducted from the bill which shall be refunded after 3 months from the date of completion of work.
3. Other taxes will be deducted as applicable time to time.

  
Sub-Divisional Engineer (Elect.)  
M.D. University, Rohtak. 



SDE/(Elect.)/2023/ 353-55 Dated 25/8/23

Cope of the above is forwarded to the following for information and necessary action:-

The Executive Engineer, M.D. University, Rohtak

Notice Board

Contractors/Agencies

  
Sub-Divisional Engineer (Elect.)  
M.D. University, Rohtak. 

DNIT for "S/E of LED false ceiling light 36 watt for Admin Block UIET, Room No. 205, Pharmacy Science & G-23 Lab Genetic Department in MDU, Rohtak".

Sr.no	HSR/NS	Description of items	Qty	Unit	Rate to be quoted by Agency
1	23.2	Fixing of LED tube light 2 x 2 feet square panel fitting directly on wall / ceiling or false ceiling including making connections etc as required	24	Nos.	
2	NS- 1	Supply of recess mounted 36 watt LED flat panel 600 MM x 600 MM, Lumen of above in cool day light (5700K to 6500K), Average life > 50000 Hrs. power factor . 0.95, CRI . 80, LED lamp efficacy > 100 LM/Watt, System lumen should be > 3600 and glare free opal diffuser and housing made of CRCA sheet steel finishing with epoxy powder coating complete in all respect to the satisfaction of Engineer-in-charge. Make- Philips/Havells/Bajaj	24	Nos.	
3	NS- 2	Credit of old coventional type 600 MM x 600 MM 36 watt false ceiling fitting	12	Nos.	